

 GSM SYSTEM

 SMS ALERT

 MOBILE APPS


eldes

CONNECTED
PROTECTED
COMFORT



READY TO USE. EASY TO USE.




Mobile applications for
iOS and Android



FREE

ELDES  CLOUD
SERVICES

CLOUD.ELDES.LT



WEB browser

REMOTE CONTROL AND MONITORING

ALARM AND SECURITY

WIRELESS AND ACCESSORIES

SOFTWARE AND SERVICES



Copyright © Eldes JSC. All Rights Reserved.



made in Lithuania, Europe

www.eldes.lt

HYBRID GSM, LAN AND PSTN CONTROL PANEL

Hybrid powerful and flexible smart home alarm system up to 300 m2 in open space.

NEW

ESIM384



- 8 zone on board
- 80 (wired + wireless) zones
- 10 phone users, 30 codes, 4 partitions
- Remote configuration with Configuration Tool
- ELDES Cloud powered
- Ways of remote control and configuration:
 - Mobile App
 - WEB
 - SMS
 - Voice call

Comes with all demanded modules and gateways onboard. Fully expandable, just in case you require more.

ESIM364



EN 50131-1
GRADE 3
CLASS II
CERTIFIED

- 6 zone on board
- 10 users, 30 codes, 4 partitions
- Up to 38 zones
- Remote configuration with Configuration Tool
- ELDES Cloud powered
- Ways of remote control and configuration:
 - Mobile App
 - WEB
 - SMS
 - Voice call

HARDWIRED ZONE & PROGRAMMABLE OUTPUT EXPANSION

EPGM1



- 16 hardwired zones
- 2 programmable outputs 500mA

HARDWIRED PROGRAMMABLE OUTPUT EXPANSION

EPGM8



- 8 programmable outputs 500mA

AUDIO AMPLIFIER MODULE

EA2



- 1 W 8 Ohm
- For Intercoms, Elevators
- Allows the connection of external wired headphones or computer speakers and enables dual voice communication for an intercom

UNIVERSAL 2G/3G COMMUNICATOR

ET083




Connect almost any alarm panel to monitoring station or add extra communication channel for mobile security.

- Supported protocols: EGR100, Ademco Contact ID, SIA IP and Kronos (GRPS)
- Firmware Over-The-Air updates
- Remote configuration of communicator
- Remote arm/disarm of the upgraded central panel
- Up to 5 users
- Provides communication via LAN/GSM/GPRS



ET083 UNIVERSAL 2G/3G COMMUNICATOR



Any alarm panel with built in PSTN

GSM/GPRS



Programming alarm panel with incoming call via DTMF



Five users can get SMS

Central Monitoring station

Monitoring software EGR100 MLR2-DG protocol

Fixed telephone line

GSM SWITCH FOR GATES, DOORS AND OTHER APPLICATIONS

DOORS, GATES, BARRIERS, PUMPS, LIGHTS, ANYTHING. CONTROLLED REMOTELY.

ESIM120



- 2000 users
- 5 administrators
- Inputs: 3
- Outputs: 2
- Remote configuration with Configuration Tool or SMS
- Cloud powered
- Ways of remote control:
 - Mobile App
 - WEB
 - SMS
 - Voice call

Call, text, use app, widget, or web, using Cloud.

WIRED KEYPAD



SLIM | STYLISH TOUCHPAD

EKB2

- Modern design with Glass Top
- Touch sensitive buttons
- LCD graphic display
- Tamper, 1 additional wired zone

COMPLETE GSM MODULE IN ONE DEVICE

EPIR3



- 10 users
- 1 hardwire zone
- Remote configuration with Configuration Tool
- ELDES Cloud powered
- Ways of remote control and configuration:
 - Mobile App
 - WEB
 - SMS
 - Voice call
- Pet immune motion sensor

GRADE II PENDING



BATTERY POWERED GSM INTRUSION CONTROL PANEL

ESIM4



- 10 users
- 2 years of battery time
- 2 inputs (4 in ATZ mode)
- 1 open collector 200mA 30V output
- 1 aux terminal (12V, 200mA)
- Connect Analog sensors (4..24mA)
- Connect Digital sensors (0..3V)
- Configuration SMS or USB
- Arm/Disarm via Call, SMS or Touch Memory interface